



NOTES:
 SEPTIC TANK MODEL # PT-1000
 • THIS TANK CONFORMS TO CAN/CSA -886-1110.
 • COMPRESSIVE STRENGTH OF THE CONCRETE SHALL BE 32.0 MPA
 • INLET DEVICE SHALL NOT EXTEND MORE THAN 125MM INTO LIQUID LEVEL.
 • BURIAL DEPTH = 3.13 METERS
 • WORKING RETENTION CHAMBER CAPACITY = 3370 L (890 GAL)
 • WORKING PUMP OUT CHAMBER CAPACITY = 1100 L (290 GAL)
 • TOTAL WORKING CHAMBER CAPACITY = 4545 L (1200 GAL)

GENERAL NOTE-
 • CHAMFER 30MM @ 45° UNLESS OTHERWISE SPECIFIED TOLERANCES ±2.0MM
 • IF THE TANK IS SET ON UNLEVEL SURFACE, THE BOTTOM OF THE EXCAVATION NEEDS TO BE LEVELED WITH AGGREGATE IN ORDER TO SUPPORT THE TANK EVENLY.
 • IF THE TANK HAS AT LEAST 12" OF GROUND COVER OVER THE TOP OF IT, THERE IS NO OTHER BALLAST REQUIRED.

barkmanTM

152 Brandt Street, Steinbach, MB R5G 0R2
 T (204) 326 3445 or 1 800 461 2278 F (204) 326 5915
 barkmanconcrete.com

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BARKMAN CONCRETE LTD. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BARKMAN CONCRETE LTD. IS PROHIBITED.

CUSTOMER
barkman STD PRODUCT

PROJECT
1000 GALLON SEPTIC PUMP TANK

TITLE
PRODUCT DETAILS

PART NUMBER		110912		
	INITIALS		MM/DD/YYYY	
DRAWN BY	DST	DATE	06/11/2013	
CHECKED BY		DATE		
WEIGHT (lbs)	SCALE	PAPER SIZE	SHT NO.	REV. #
11,770	N.T.S.	8 1/2 X 11 (A)	1	0