




SPLITNSTACK ® System Units					
	Face Width	Back Width	Height	Depth	Weight
 Standard Unit	8"	6"	4"	8"	18 lbs
	200 mm	150 mm	100 mm	200 mm	8.1 kg
 Corner Unit	8"	6"	4"	8"	18 lbs
	200 mm	150 mm	100 mm	200 mm	8.1 kg
 Coping Unit	8"	6"	4"	8"	18 lbs
	200 mm	150 mm	100 mm	200 mm	8.1 kg

SPLITNSTACK ® System Design/Construction Information			
Minimum Inside/Outside Radius (tapered units)	Inside Radius (Bottom Course)	1.9'	
		575 mm	
	Outside Radius (Bottom Course)	2.5'	
		775 mm	
Maximum Gravity Height		2.0'	
		610 mm	
Maximum Geogrid Height		N/A	
		N/A	
Application of Handrail		N/A	
		N/A	
Application of Wood Fence		N/A	
		N/A	
Application of Coping Unit		Use Adhesive	
Stacking Alignment		Vertical	
Facing		Split Face	
Placement Method		Hand	

RomanStack®
Retaining Wall
System



RisiStone®
retaining wall systems

8500 Leslie Street, Suite 390
Thornhill, Ontario
Canada, L3T 7M8
Tel 905.882.5898 Fax 905.882.4556
<http://www.risistone.com>
©2002 Risi Stone Systems

SKSYS.DWG