




Step 1. Compacted infill level with top of SRW block.



Step 2. Place geogrid on top of block within 25mm (1") of face.
For most Risi Stone blocks, the geogrid will be placed past the front edge of the chamfer (as shown).




Step 3. Secure geogrid in place at face with next course and pull geogrid taut. Maintain tension with temporary stakes as shown.



Notes:

1. Follow geosynthetic manufacturer's installation instructions and specifications. Care must be taken to ensure geogrid is not damaged during construction or subject to UV exposure.
2. Do not allow ANY tracked equipment directly on top of the geogrid. For necessary travel on the geogrid, use only lightweight rubber tired equipment operating at slow speeds (less than 10 mph); do not allow braking or sharp turning.
3. Geogrid length, placement and type shall be as indicated in the Wall Design.
3. Geogrid must be placed in direction of highest strength (roll direction) perpendicular to face of wall. (i.e. - Do not roll out geogrid along the length of the wall).
4. **COMPACTED INFILL MUST BE LEVEL WITH THE TOP OF THE BLOCK PRIOR TO PLACEMENT OF GEOGRID.**
5. Remove all debris from the top of the SRW block prior to placement of geogrid.
6. Geogrid must be placed within 25mm (1") of the front face of the block.
7. Geogrid must be pulled taut, removing any slack or wrinkles prior to the placement of infill material. The use of temporary stakes to maintain tension of the geogrid is good practice. Infill material should be dumped close to the face of the wall and raked away from the wall to maintain tension in the geogrid during backfilling. When infill material is placed, caution must be used to ensure hand equipment (shovels and rakes) does not contact the geogrid or cause damage.
8. Adjacent sections of geogrid shall abut eachother (not overlap or gap) at the face of the wall to ensure continuous geogrid coverage. Geogrid cannot be spliced to create the required length into the back - the geogrid must be one continuous piece.
9. **Do not stack more than two (2) courses of block prior to backfilling wall.**

Step 4. Place infill material near face of wall and spread back, away from wall to maintain geogrid tension. Compact infill material in max. 150mm-200mm (6"-8") lifts. Continue process to next geogrid layer.



RisiStone[®]
retaining wall systems

ArchitexturesXL[®]
Geogrid Installation Sequence

<http://www.risistone.com>

©2019 Risi Stone Systems

AXLDET008.DWG